



Koch Filter Corporation
Filtration Products Crafted with Pride

Bulletin No. K 386D

Supergrade Fiberglass

Air Filter Media



Koch Supergrade Fiberglass Air Filter Media is available in a wide range of pad and roll sizes. Because all air filtration systems are different, one standard media cannot meet every requirement. With three media depths to choose from it is possible to find the right media for any fiberglass application. Contact your Koch representative for recommendations on your system.

Description

Although 1", 2" and 4" Supergrade Fiberglass Air Filter Medias are designed for different applications, several qualities are common to all three styles:

Progressive Density

All Koch fiberglass media consists of continuous filaments of high quality spun glass. These fibers are formed into a graded density blanket to provide maximum depth loading throughout the roll or pad.

Special Adhesive

Each individual fiber is coated with a specially designed adhesive gel. This adhesive enhances the media's dust holding ability by creating a "wicking" action not provided by competitive medias.

Color Coded Media

All Koch Fiberglass Media is tinted on the air entering side for easy installation into frames or blanket systems.

1" and 2" Media- White, upstream; Blue, downstream

4" Media- White, upstream; Yellow/Gold, downstream

Supergrade Media Product Performance Data

MEDIA DEPTH	AVG ARRESTANCE ¹	DUST HOLDING CAPACITY ²	INITIAL RESISTANCE	RECOMMENDED VELOCITY (FPM)	MERV RATING ²
1"	66%	127 GRAMS	.035 IN W.G.	350	3
2"	72%	154 GRAMS	.065 IN W.G.	350	3
4"	85%	260 GRAMS	.18 IN W.G.	500	4

¹ Based on ASHRAE Test Method 52.1

² Based on ASHRAE Test Method 52.2

Corporate Offices

P.O. Box 3186 • 625 West Hill Street (40208) • Louisville, KY 40201 • 502.634.4796 • Fax: 502.637.2280 • E mail: info@kochfilter.com • www.kochfilter.com

Distribution Centers

Louisville • Charlotte • Cincinnati • Denver • Houston • Indianapolis • Kansas City • Nashville • St. Louis

© 2002 KOCH FILTER CORPORATION